

PAARD

Audio specs MAIN HALL

June 2018

Stage empty: 14.4 x 7,85 x 1,2m (clearance 9m).

Stage with House PA: 10.5 x 7,85 x 1,2m (clearance 9m).

Power (Sound Only): Stageleft: 1x 63A (5 pin-3Ph) and 1x 32A (5pin-3Ph).
Stageright: 1x 32A (5pin-3Ph).

P.A. system: 8x Adamson E12 flown per side.
5x Adamson E119 subwoofer flown per side.
1x Adamson E119 subwoofer stacked per side.
2x Adamson M12A per side, front- and outfill.
1x Adamson Point8A per side, 2nd balcony fill.
Lab Gruppen amplifiers.

Drive: 2x Lake LM-44 audio processor.
TabletPC for use of Lake Controller.
Standard drive output: TOP L, TOP R, FILL L, FILL R, SUB on AES/EBU or analogue.
[delay- and x-over settings are locked]

FOH console: DiGiCo SD-5cs, CORE2, V987.
Local I/O: 8 x Mic/Line I/O, 8 x AES I/O
Waves card.
[request wauter@paard.nl for housefile]

FOH rack (on stage): DiGiCo SD-Rack 192 kHz.
56x Mic/Line input (32bit), 24 Lineout, 8 AES out.

Note: The venue has a sound pressure limit of 103 dB(A) LEQ-15 @ F.O.H. position. We expect sound engineers to respect this limit.

Paard, The Hague, The Netherlands

Prinsegracht 12 Den Haag | phone: +31(0) 70 750 34 34 | fax: +31-(0) 70 363 03 57 |

- MON console:** DiGiCo SD-5cs, CORE2, V987.
Local I/O: 8 x Mic/Line I/O, 8 x AES I/O.
[request wauter@paard.nl for housefile]
- MON rack:** DiGiCo D2-Rack with 48x Mic/Line input, 24 Lineout, 8 AES out.
- MON system:** 14x D&B floor monitor M4 including 2x PFL.
8x D&B D-80 amplifiers.
4x D&B B4 sub.
14x active 2-way mixes including subs and PFL.
- Microphones:** 1x Shure b91
2x Shure b52
8x Shure sm57
3x Shure b56a
5x Sennheiser e904
4x Shure ksm137
2x AKG c214
1x Neumann km184
3x Sennheiser md421
2x Sennheiser e906
2x Shure b57a
12x Shure sm58
3x Shure b58a
- Microphone stands:** 12x short boom
24x tall boom
1x tall roundbase
- D.I. boxes:** BSS: 8x AR133
Radial: 4x Pro DI.
KlarkTeknik: 2x LBB100.
ASL: 2x dual transformer.
- Miscellaneous:** Stagebox with 48 lines, parallel outputs, 1 socapex connector per 12 channels
Intercom system (ASL).
220v to 110v step down converter. Max load 1200 W.
(Rolling) riser: various heights and sizes available.
- Passive recording feed available from the stage box on XLR male connectors.
Other possibilities upon request.*

Note: The venue has a sound pressure limit of 103 dB(A) LEQ-15 @ F.O.H. position. We expect sound engineers to respect this limit.

Paard, The Hague, The Netherlands

Prinsegracht 12 Den Haag | phone: +31(0) 70 750 34 34 | fax: +31-(0) 70 363 03 57 |